

# Professional Projector

## Series LM 51




knowledge exchange power



LM New Series are multifunction models of diverse utilities including education, business and home entertainment. By developing inorganic 3LCD panel's 4:3 for 0.79 panel, the series deliver sharp and brilliant image with high brightness up to 6000 Ansi Lumens. Optimized cooling and dust proof design with less than 1 watt in power save mode standby. LM 51 energy saving and environmental friendly in operation.

- 3LCD Technology
- Direct power on/off
- 1/4 ~ 16 Digital Zoom
- High Contrast 2000:1
- Top drawer lamp replacement
- RJ45 network control
- Support WXGA, UXGA and Mac Resolution
- Vertical and Horizontal keystone correction
- Four corner correction
- Wifi and USB Display Function
- Auto adjust the lamp brightness according to the input signal.



## SPECIFICATIONS



### Features

1. One Touch change Lens
2. Auto Focus
3. USB Display
4. Wifi Display
5. One Key set auto focus  
Input search, Auto PC adjust, Auto keystone
6. Horizontal keystone, Four corner keystone
7. Auto Power-Off on Signal , Sourcing Failure
8. Tripple Filter (Sponge/ESD/ESD)
9. High speed power off


### Remote Control (Card Type)

### OSD Languages

English, French, Spanish, Portuguese, Dutch, Italian, Japanese, Korean, Russian, Finnish, Dutch, Thai, Vietnamese, Turkish, Afrikaans, Bahasa, Indonesia, Farsi, Arabic, Chinese.

### Standard Accessories

User Manual (CD), Power Cord, Remote Control & battery, VGA cable, Warranty card, Qualified card, Drying agent



### Description

### LM 51

<b>Display Technology</b>	Liquid Crystal Display Panel
<b>Display Panel</b>	0.79" TFT active matrix type, 3 panels
<b>Brightness (ANSI Lumens)</b>	6000
<b>Native Resolution</b>	XGA (1024 x 768)
<b>Contrast Ratio</b>	2000 : 1
<b>Projection Lens</b>	1.6x Optics, F=1.7 -2.2,f=21.3~34.16mm,1/4~16 Digital zoom
<b>Uniformity</b>	90%
<b>Throw Ratio</b>	60" @ 1.58M
<b>Throw Distance</b>	1.025M ~ 17.48M (40" ~ 400")
<b>Aspect Ratio</b>	4:3 (Standard) / 16:9 (Compatible)
<b>Keystone (Vertical)</b>	Auto, Manual Keystone : ±30°
<b>Keystone (Horizontal)</b>	Manual Keystone : ±30°
<b>Lens shift adjustment (Vertical)</b>	+/- 50%
<b>Lens shift adjustment (Horizontal)</b>	+/- 10%
<b>I/O Port</b>	
- Computer (Input)	VGA x 2 Port
- Computer (Output)	VGA (Share Input 2)
- HDMI	x 3
- BNC X 5	x 1
- DISPLAY PORT terminal	DP-D 20 pin x 1
- Component YCbCr	x 1
- C-Video	Video x 1 (Share to YCbCr)
- S-Video (Input)	Mini DIN 4 pin x 1
- Mini Jack Audio (Input)	x 2
- Audio L/R (Input)	x 1
- USB type A	x 1 (read JPEG)
- USB type B (Display Port)	x 1 (Share with input interface)
- RS232	D-sub 9 pin x 1
- RJ45 (Display Port)	x 1
<b>PC Compatibility</b>	VGA, SVGA, XGA, SXGA, WXGA, UXGA
<b>Video Compatibility</b>	PAL, SECAM, NTSC, NTSC4.43, PAL-M, PAL-N 1080p, 1080i, 1035i, 720p, 576p, 480p, 576i and 480i
<b>Lamp</b>	275W
<b>Lamp Life (Normal / Economic)</b>	2000hrs (Normal) / 3000hrs (Economic)
<b>Net Weight</b>	8.5 Kg
<b>H~frequency</b>	15kHz ~ 100kHz
<b>V~frequency</b>	50Hz ~ 120Hz
<b>Speaker</b>	x1 (10W RMS 8 ohm)
<b>Dimension</b>	406.9mm x 151.0mm x 425.1mm
<b>Warranty</b>	2 years, Lamp warranty 1 year or 1,000 hrs whichever comes first

\* Feature and Specifications are subject to change without notice.



knowledge exchange power

บริษัท สยามเทค แอนด์ ดีไวส์ จำกัด

16/60 ถ.ติวานนท์ ต.บางพลู อ.ปากเกร็ด จ.นนทบุรี 11120

โทร. 0-2582-2285 แฟกซ์. 0-2582-2286

<http://www.gygar.com>